



Mill Backing Lining Rubber

Mill Backing Lining Rubber is a superior grade wear resistant 60 Duro rubber lining with a buffed back.

FEATURES

Mill Backing Lining Rubber is made from a premium rubber compound and will display moderate resistance to sliding abrasion and impact.

Mill Backing has good physical properties including cut and tear resistance. It will also display resistance to some mild chemicals, including acids and alkalis used in mineral processing. It has good ozone/UV resistance making it suitable for outdoor use.

Mill Backing features a pre-buffed finish on one side to assist with adhesion when bonded to steel or rubber surfaces. It can be bonded using a wide range of Neoprene based rubber adhesives.



TECHNICAL INFORMATION

Polymer	NR/BR	
Colour	Black	
Specific Gravity	1.25	ASTM D297
Hardness	65° ± 5° Shore A	ASTM D2240
Tensile Strength	10 MPa (min)	ASTM D412
Elongation @ Break	300% (min)	ASTM D412
Abrasion	180mm ³ (max) @ 10N	ASTM D5963
Temperature Range	-20°C to + 70°C	
Tear Strength	30 N/mm (min)	ASTM D624

AVAILABLE SIZES

Mill Backing Lining Rubber can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes and gaskets to suit your application requirements.

PART NO.	DESCRIPTION	WEIGHT (PER L/M)
MB061200	6mm x 1200mm (10 L/M Rolls)	9.7 kgs