

R-Line 38 Premium Lining Rubber

R-Line 38 Lining Rubber is a premium grade wear resistant 38 Duro rubber lining with a buffed back.

FEATURES

R-Line 38 Lining Rubber is made from a highly elastic premium natural rubber compound and will display excellent resistance to wet slurry and fine particle sliding abrasion.

R-Line 38 has excellent physical properties including cut and tear resistance and is extremely flexible. It will also display resistance to some mild chemicals, including acids and alkalis used in mineral processing.

R-Line 38 features a pre-buffed finish on one side to assist with adhesion when bonded to steel or rubber surfaces. It can be bonded using a wide range of Neoprene based rubber adhesives.



TECHNICAL INFORMATION

Polymer	NR	
Colour	Pink with buffed back	
Specific Gravity	0.97	ASTM D297
Hardness	38° ± 5° Shore A	ASTM D2240
Tensile Strength	22 MPa (min)	ASTM D412
Elongation @ Break	750% (min)	ASTM D412
Abrasion	75mm³ (max) @ 5N	ASTM D5963
Temperature Range	-20°C to + 70°C	
Tear Strength	35 N/mm (min)	ASTM D624



AVAILABLE SIZES

We stock R-line 38 Premium Lining Rubber in a range of standard thicknesses and roll sizes. It can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes and gaskets to suit your application requirements.

PART NO.	DESCRIPTION	WEIGHT (PER L/M)
REGBB3803	3mm x 1200mm (10 L/M Rolls)	3.8 kgs
REGBB38031500	3mm x 1500mm (10 L/M Rolls)	3.8 kgs
REGBB3806	6mm x 1200mm (10 L/M Rolls)	7.5 kgs
REGBB38061500	6mm x 1500mm (10 L/M Rolls)	9.4 kgs
REGBB3810	10mm x 1200mm (10 L/M Rolls)	12.5 kgs
REGBB38101500	10mm x 1500mm (10 L/M Rolls)	15.7 kgs
REGBB3812	12mm x 1200mm (10 L/M Rolls)	14.8 kgs
REGBB38121500	12mm x 1500mm (10 L/M Rolls)	18.5 kgs
REGBB38201500	20mm x 1500mm (10 L/M Rolls)	30.9 kgs